

(12) United States Patent

Miller et al.

US 6,972,407 B2 (10) Patent No.:

*Dec. 6, 2005 (45) **Date of Patent:**

(54) METHOD AND APPARATUS FOR **ELECTROSPRAY AUGMENTED HIGH** FIELD ASYMMETRIC ION MOBILITY **SPECTROMETRY**

(75) Inventors: Raanan A. Miller, Brookline, MA (US); Erkinjon G. Nazarov,

Lexington, MA (US); Gary A. Eiceman, Las Cruces, NM (US); Evgeny Krylov, Las Cruces, NM (US)

Assignee: The Charles Stark Draper

Laboratory, Inc., Cambridge, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

Appl. No.: 10/734,499 (21)

Filed: Dec. 12, 2003 (22)

(65)**Prior Publication Data**

US 2004/0124350 A1 Jul. 1, 2004

Related U.S. Application Data

Continuation of application No. 10/123,030, filed on Apr. 12, 2002, now Pat. No. 6,690,004, which is a continuation-in-part of application No. 09/358,312, filed on Jul. 21, 1999, now Pat. No. 6,495,823, and a continuation-in-part of application No. 09/439,543, filed on Nov. 12, 1999, now Pat. No. 6,512,224, and a continuation-in-part of application No. 09/799,223, filed on Mar. 5, 2001, now Pat. No. 6,815,668, and a continuation-in-part of application No. 10/040,974, filed on Jan. 7, 2002, now abandoned.

(51) Int. Cl.⁷ B01D 59/44

(52) U.S. Cl. 250/287; 250/286; 250/282;

250/288

250/282, 288

(56)References Cited

U.S. PATENT DOCUMENTS

10/1952 Glenn 2,615,135 A 2,818,507 A 12/1957 Britten

(Continued)

FOREIGN PATENT DOCUMENTS

SU966583 A 10/1982 9/1987 SU 1337934 A2

(Continued)

OTHER PUBLICATIONS

"Comparison of the Planar and Coaxial Field Asymmetrical Waveform Ion Mobility Spectrometer (FAIMS)," International Journal of Mass Spectrometry, 225, (223), pp. 39-51.

Primary Examiner—John R. Lee Assistant Examiner—Zia R. Hashmi (74) Attorney, Agent, or Firm-Ropes & Gray LLP

ABSTRACT

A field asymmetric ion mobility spectrometer apparatus and system including a sample preparation and introduction section, a head for delivery of ions from a sample, an ion filtering section, an output part, and an electronics part wherein the filter section includes surfaces defining a flow path, further including ion filter electrodes facing each other over the flow path that enables the flow of ions derived from the sample between the electrodes and wherein the electronics part applies controlling signals to the electrodes for generating a filter field for filtering the flow of ions in the flow path while being compensated to pass desired ion species out of the filter.

14 Claims, 33 Drawing Sheets

